



JA-110TP Bus indoor thermostat

In a building, up to 16 thermostats can be installed that can control up to 16 independent circuits. The product is a component of the JABLOTRON 100+ system, is addressable and occupies one position in the system.

○ [Declaration of conformity - JA-110TP \(PDF 315.52 kB\)](#)

Description

- Full integration in MyJABLOTRON = information of the current status and remote control of the thermostat
- Automatic switch-over to the economy temperature on setting the premises
- Weekly schedule mode
- Possibility to enter the manual temperature setting mode
- Possibility to switch off if only a minimum temperature should be maintained in the building
- Heating suppression if a window is open
- Report in the case of overheating or freezing
- Easy control by dial
- Temperature history graph
- Tamper sensor

Technical specifications

Power	from control panel BUS 12 V (9...15 V)
Current consumption in standby mode	1.5 mA
Current consumption for cable choice	1.5 mA
Dimensions	66 x 90 x 22 mm
Weight	60 g
Operational temperature range	-10 °C to +70 °C
Measuring range	-10 °C to +70 °C
Temperature regulator class	I. (according to (EU) no. 813/2013)
Contribution of regulator for seasonal efficiency	$\eta_S = 1\%$ (according to (EU) no. 813/2013)
Operational environment according to	EN 50131-1 II. Indoor general

Temperature measuring sensitivity

±0.1 °C

Also complies with

EN 50130-4, EN 55022