



## JA-120PC (90) Bus PIR motion detector with 90° photo-verification camera

Used for motion detection inside buildings, including visual alarm confirmation. Taking a photo is activated by motion, so the cause of the alarm is always indicated in the image. Guaranteed detection coverage 90°/12 m.

○ [Declaration of conformity - JA-120PC \(90\) \(PDF 316.26 kB\)](#)



### Description

- Vision angle of the camera: 90°
- Resolution of photos: LQ 320\*240; HQ 640\*480 pixels
- Flash range: max. 3 metres
- Power via the control panel bus
- The detector has impulse activation
- The detector can be used to control programmable PG outputs
- The resistance to false alarms is adjustable to two levels
- The detector is a component of the JABLOTRON 100+ system, is addressable and occupies one position in the system

### Technical specifications

<b>Power</b>	from the control panel BUS +12 V (+9 ... +15 V)
<b>Current consumption</b>	
- nominal for the backup supply calculation	5 mA
- maximum for cable choice	250 mA (with high flash intensity)
<b>Recommended installation height</b>	2.5 m above the floor
<b>PIR detection angle/detection coverage</b>	90°/12 m
<b>Horizontal camera capture angle</b>	90°
<b>Range of the flash</b>	max. 3 meters
<b>Camera resolution</b>	LQ 320x240; HQ 640x480 pixels
<b>Photo size LQ/HQ (typically)</b>	2-20 kB/2-64 kB (6 kB/35 kB)
<b>Typical (LQ) photo transmission time to the control panel</b>	up to 20 s. (10 s)

<b>Ideal (HQ) photo transmission time to the control panel</b>	up to 130 s (60 s)
<b>Typical photo transfer time to the server</b>	15 s/GPRS; 2 s/LAN
<b>Dimensions, weight</b>	110 x 60 x 55 mm, 102 g
<b>Classification</b>	Security grade 2/Environmental class II
<b>- according to</b>	EN 50131-1, EN 50131-2-2
<b>- operational temperature range</b>	-10 °C to +40 °C
<b>- operational environment</b>	indoor general
<b>- certification body</b>	Trezor Test s.r.o. (no. 3025)
<b>Also complies with</b>	EN 50130-4, EN 55032