



JA-122PW-AN Bus dual PIR and MW motion detector - anthracite

This product is a bus device of the JABLOTRON 100+ system. It is designed to detect human body movement inside buildings. A high immunity to false alarms is reached thanks to the combination of PIR and microwave (MW) detection. The detector works like a classic PIR detector, however, when the PIR detects movement in a guarded area, the MW part is activated and confirms the previous PIR activation.

○ [Declaration of conformity - JA-122PW-AN \(PDF 676.13 kB\)](#)

Description

The product features a white lens that provides standard white light immunity as defined by the norm (up to 6000 lux). The immunity to false alarms can be set at two levels, PIR and MW. The detector operates with a pulse reaction and takes up a single position in the system.

Technical specifications

Power supply

from the control panel bus 12 V DC (9 ... 15 V)

Current consumption
- in standby mode

5 mA

- for cable choice

16 mA

Recommended installation height

2.2 - 2.5 m above floor level

Detection angle/PIR coverage

90°/12 m

Detection angle/MW coverage

80°/12 m

MW Frequency

24.125 GHz

Maximum MW radio-frequency power (ERP)

30 mW

Dimensions:

150 x 63 x 40 mm

Weight

120 g

Classification

Security grade 2/Environmental class II (According to EN 50131-1)

Environment

Indoor general

Operating temperature range

-10 °C to +40 °C

Average operational humidity

75 % RH, w/o condensation

Certification body

Trezor Test s.r.o. (no. 3025)

In compliance with

ETSI EN 300 440, EN 50130-4, EN 55032, EN 62368-1, EN 50581, EN 50131-1, EN 50131-2-4

Operating conditions according to general authorization

ERC REC 70-03