



## JA-150M-AN Wireless magnetic detector with 2 universal inputs - anthracite

It is a magnetic detector with two configurable independent inputs. The detector is also designed to detect the handling of roller blinds, if it is equipped with a CT-01 roller detector.

### Description

Small movements are filtered out so that wind blasts do not cause false alarms. It occupies two separate enrollment addresses in the control panel. The product can be installed by a certified technician with a valid certificate issued by an authorized distributor.

### Technical specifications

**Power**

1x alkaline battery type LR6 (AA) 1.5 V  
Please note: Battery is not included

**Typical battery lifetime**

about 2 years

**Communication band**

868.1 MHz, JABLOTRON protocol

**RF range**

approx. 300 m (open area)

**The maximum length of cable for external detectors**

3 m

**Maximum radio-frequency power**

10 mW

**Dimensions**

109 x 24 x 22 mm

**Classification**

Grade 2

**According to**

EN 50131-1, EN 50131-3, EN 50131-2-6, EN 50131-5-3

**Operational environment**

EN 50131-1 II. Indoor general

**Operational temperature range**

-10 °C to +40 °C

**Also complies with**

ETSI EN 300220, EN 50130-4, EN 55022, EN 50950-1

**Can be operated according to**

ERC REC 70-03

