



JA-151ST Wireless combined smoke and heat detector with built-in siren

It is used **to detect fire hazards in the interior of residential or commercial buildings**. The detector can be installed in mobile homes or caravans. The product is not designed to be installed in industrial premises.

- [Declaration of conformity - JA-151ST \(PDF 1.48 MB\)](#)
- [Declaration of performance - JA-151ST \(PDF 287.09 kB\)](#)

Description

The JA-151ST detector uses wireless communication and it is powered with three AA batteries. The detector should be installed by a trained technician with a valid with a valid manufacturer's certificate.

The detector indicates a fire hazard using the built-in LED indicator and acoustic signalling.

The JA-151ST consists of two independent detectors - an optical smoke detector and a heat detector. The optical smoke detector works on the principle of scattered light. It is very sensitive to large dust particles which are present in dense smoke. It is less sensitive to smaller particles generated by the combustion of liquids such as alcohol. That is why the fire detector also contains a built-in heat detector which has a slower reaction but is much better at detecting fire which generates only a small amount of smoke.

Technical specifications

Power

3 x Alkaline battery type LR6 (AA) 1.5 V/2.4 Ah
 Please note: Batteries are not included

Typical lifetime

approx. 3 years

Smoke detection

optical light scattering

Smoke detector sensitivity

$m = 0.11 \div 0.13$ dB/m
 pursuant to EN 14604:2005, EN 54-7

Heat detection

class A1 according to EN 54-5

Alarm temperature

+60 °C to +65 °C

Communication band

868.1 MHz, Jablotron protocol

Effective Radiated Power (ERP)

10 mW

Communication range

approx. 300 m (unrestricted area)

Dimensions

diameter 126 mm, height 50 mm

Weight

150 g

Operating temperature range

-10 °C to +65 °C

Also complies with

EN 54-25, ETSI EN 300 220, EN 60950-1, EN 50130-4 and EN 55022.

Can be operated according to

ERC REC 70-03

Recommended screw

2x \varnothing 3.5 x 40 mm (countersunk head)
