



OS-365A Outdoor siren

The **OS-365A** is a **hard-wired outdoor backed-up siren** combining a **loud acoustic siren** with a **flashing light**. The high-powered flashing light helps to locate the active siren.

○ [Declaration of conformity - OS-365A \(PDF 315.27 kB\)](#)

Description

The **OS-365A** is equipped with a **magneto-dynamic horn siren** mainly suitable for family houses or for buildings with more space around them. **Two tamper switches** are built into the unit. They react to removing the cover from the unit or removing the siren from the wall. The siren's housing is made of mechanical-, weather- and UV-resistant plastic. The circuit board is protected against air humidity by a double layer of varnish.

Technical specifications

Power supply	10 to 15 V DC
Standby consumption	< 50 mA/12 V
Maximum load consumption	< 800 mA/12 V
Backup battery	NiCd pack 4.8 V/1800 mAh Lifetime approx. 3 years
Electro-acoustic siren sound level	110 dB/1 m
Siren timer	max. 5 minutes
Flasher time	alarm duration +15 minutes/0
Resistance of the tamper loop	< 70 Ohms
Enclosure	IP 34D
Security grade 2	EN 50131-1, CLC/TS 50131-4
Working environment	class IV, outdoor general
Operational temperature	-25 to +60°C
EMC	EN 50130-4, EN 55022
Safety	EN 60950-1

Dimensions

230 x 158 x 75 mm